

TOWN OF HUDSON

FIRE DEPARTMENT - INSPECTIONAL SERVICES DIVISION

12 School Street • Hudson, New Hampshire 03051 • Tel: 603-886-6005 • Fax: 603-594-1142

TANK INSTALLATION PERMIT APPLICATION

		Office Use:
Installation Address:		Permit#:
Business Name:	Unit:	Map:
Type of Occupancy: Residential \square Comm	nercial/Industrial \square	Lot:
Estimated Cost: Perm	it Fee:	Zone:
Tank Location*: Above Ground \square Under Ground** \square Fuel: Propane \square Oil \square		
Tank: New \square Replacement \square Gas Lines: Existing \square New \square		
Tank Size: Number of Tanks: Tank Serial #:		
Tank Owner:		
Tank Owner's Address:		
Phone #: Email:		
Property Owner:	Contractor:	
Mailing Address:	Mailing Address:	
Daytime Phone #:	——————————————————————————————————————	
Cell Phone #:	Cell Phone #:	
Email:	Email:	
*A site plan and or drawing of tank placement must be attached to this document. The plan / drawing must include the following: main road, driveway, house location and adjacent lot line with approximate dimensions to all. ** All underground installations must be inspected by an Inspectional Services representative prior to backfilling of excavation.		
My signature indicates that residential installations have met all requirements as stated in the NFPA Standard 58 LP Gas Code, latest edition adopted by the NH State Fire Marshal's Office and all applicable state and local laws, ordinances, regulations and standards. My signature also indicates that commercial and industrial installations have met all the above mentioned codes in addition to NFPA 30 Flammable and Combustible Liquid Code and NFPA 54 National Fuel Gas Code.		
Signature of Installer	Date	
Signature of Permit Clerk	 Date	



12 School Street • Hudson, New Hampshire 03051 • Tel: 603-886-6005 • Fax: 603-594-1142

TANK INSTALLATION REQUIREMENTS

Oil Tanks

- 1. Maximum inside capacity shall not exceed 660 gallons.
- 2. Tank shall be at least 5 feet away from open flames or fuel burning appliances.
- 3. Tank shall be located at least 3 feet away from any electrical panels or shutoff valves.
- 4. Fill pipe shall be at least 1¹/₄ inch.
- 5. Fill and vent pipes shall terminate at least 2 feet from building openings.

Propane Tanks - Aboveground

- 1. Tank shall be installed to the requirements of the currently adopted edition of NFPA-58 and by qualified installers.
- 2. 125-500 gallon tanks shall be at least 10 feet away from structures and property lines.
- 3. 501-2000 gallon tanks shall be at least 25 feet away from structures and property lines.
- 4. Tanks shall be 10 feet from any source of ignition.
- 5. Tanks shall be 5 feet from building openings.

Propane Tanks - Underground

- 1. Tank shall be installed to the requirements of the currently adopted edition of NFPA-58 and by qualified installers.
- 2. Cathodic protection for tank.
- 3. All underground installations must be inspected by Inspectional Services prior to back-filling of excavation.
- 4. Rock and abrasive free back fill on site.
- 5. 2000 gallon or less shall be 10 feet from buildings, openings, property lines and/or ignition sources.
- 6. Gas line trench shall be at least 12 inches deep.